



TECHNICAL DATA SHEET

AMPAC Air Tool Tool Lubricants

PRODUCT DESCRIPTION:

AMPAC Air Tool Lubricant provides not only superior lubrication, but dissolves and prevents the formation of gum and varnish deposits so often associated with air tool operations.

AMPAC Air Tool Lubricant is an air tool oil that provides excellent lubrication for both rotary and reciprocating types of air tools, such as chipping hammers, impact wrenches, air motors, grinders, reamers, drills, etc. It can be fed through an airline lubricator, or applied directly into the tool through the quick coupling air connection.

Advantages

For the most in safe, simple and economical lubrication of rotary and reciprocating types of air tools, small amounts of AMPAC Air Tool Lubricant, used daily, will effectively lubricate the air tool keeping it clean and free-running.

Applications

AMPAC Air Tool Lubricant, as an air line lubricant, has been used very effectively on the lift cylinders of can fillers in breweries, bottling plants and canning plants, keeping the cylinders clean and eliminating hand cleaning.

TYPICAL PROPERTIES

AMPAC Air Tool Tool Lubricants		
Prod Code	AMO 0250	Test Method
ISO Grade	32	ASTM D-2422
Viscosity@40°C, cSt	30	ASTM D-445
@100 °F	147	ASTM D-2161
@100 °C	5	ASTM D-445
@210 °F	44	ASTM D-2161
Viscosity Index	120	ASTM D-2270
Flash Point, °C	385 °F/196 °C	ASTM D-92
Aniline Point	200 °F/93 °C	ASTM D-611
API Gravity	27.4	ASTM D-287
Pour Point	-30 °F/-34 °C	ASTM D-97