

## TECHNICAL DATA SHEET

## AMPAC – 625 Valve Stem Pak

#### **Product Description:**

**AMPAC – 625** is the base fluids provide a very low coefficient of expansion (from -  $80^{\circ}$ F to  $500^{\circ}$ F) while being oil resistant. It is most popular blend of 100% base oils with synthetic fibres and fillers that provide a sure seal.

#### **Application:**

**AMPAC- 625** is pumpable a high pressure (10,000 PSI) lubrication handgun. It can be used in hydrocarbons, steam, water, sour gas, and sour crude.



Page 1-2



# TECHNICAL DATA SHEET

### **AMPAC – 625**

Valve Stem Pak

AMPAC - 625	Valve Stem Pak
Prod Code	AMPAC 625 Valve Stem Pak
Appearance	Green, Grainy
NLGI	>6
Penetration	30-60 (ASTM D217)
Flash Point	>450°F (260°C)
Thickener	Inorganic
Base Oil	Synthetic
Base Oil Viscosity	60,000 cSt at 25°C
Solids Content	Synthetic Fiber, Fillers
Dropping Point (ASTM D566)	>500°F (260°C) (ASTM D566
Base Oil Pour Point	-40°F (-40 °C)
Temperature Range	-80°F to 500°F (-62°C to 260°C)
Specific Gravity	1.4
Density (lb/gal)	11.9