



## TECHNICAL INFORMATION SHEET

# ESCORT - HT 60

## HIGH PRESSURE / TEMPERATURE GREASE

### TECHNICAL DATA :

The ESCORT - 60 of lubricants are also listed as 'MULTI-PURPOSE' but with a higher operating temperature range than any other lubricants.

ESCORT - HT 60 possess high film strength and exceptional resistance to water, steam, and other adverse operating conditions. Since these lubricants are of the non-melt type, they can be used successfully for high temperature applications up to 375°F, and short intervals up to 400°F.

The ESCORT - HT 60 of lubricants are shear stable Multi-purpose Grease for plain and anti-friction bearings. These lubricants are recommended wherever microgel greases, bentone greases, urea greases, and complex greases are recommended and used.

ESCORT - HT 60 is a N.L.G.I No. 2 lubricant for general greases gun application.

### TYPICAL TESTS :

TYPE OF THICKENER	:	Gelling Agent
N.L.G.I NO.	:	2
WORKED PENETRATION RANGE @ 77°F	:	265 / 295
ASTM DROPPING POINT °F	:	Non-Melt Type
MINERAL OIL VISCOSITY SUS @ 100°F	:	750
CST 40°C	:	135
NON-CORROSIVE EXTREME PRESSURE & LUBRICITY	:	YES
WATER RESISTANT	:	YES
COLOUR	:	Off-White

